

BARRE TONDE

EN AW 7075 T6


EN AW 6082 T6

EN AW 2011 T3/T6

DIMENSIONE in mm	Kg/m
4	0,035
5	0,055
6	0,079
7	0,107
8	0,14
9	0,178
10	0,219
11	0,266
12	0,316
13	0,371
14	0,431
15	0,494
16	0,562
17	0,635
18	0,712
19	0,793
20	0,879
21	0,969
22	1,064
23	1,163
24	1,266
25	1,374
26	1,486
27	1,603
28	1,724
29	1,849
30	1,979
31	2,113
32	2,251
33	2,394
34	2,542
35	2,693
36	2,85
37	2,98
38	3,175
39	3,344
40	3,518

DIMENSIONE in mm	Kg/m
42	3,879
43	4,066
44	4,257
45	4,552
46	4,653
48	5,066
50	5,697
52	5,946
55	6,652
56	6,896
57	7,144
58	7,397
60	7,916
65	9,291
70	10,775
75	12,37
80	14,074
85	15,888
90	17,813
95	19,837
100	21,991
105	24,245
110	26,609
115	29,083
120	31,667
125	34,344
130	37,165
135	38,6
140	43,102
150	49,48
155	51
160	56,297
165	58
170	63,554
175	64,943
180	71,251
190	79,347





BARRE TONDE

EN AW 7075 T6
EN AW 6082 T6
EN AW 2011 T3/T6

DIMENSIONE in mm	Kg/m
200	85
210	96,9
220	106,4
230	116,3
240	126,6
250	137,4
260	148,6
270	160,3
280	172,4
290	184,9
300	197,9

DIMENSIONE in mm	Kg/m
310	211,3
320	225,1
330	239,4
340	254,2
350	269,3
360	285
380	317,5
400	351,8
420	387,9
450	455,2
500	549,7